

## PACKING INSTRUCTION Y344

STATE VARIATIONS: BEG-03, OMG-03, SAG-01, USG-04, YEG-05

OPERATOR VARIATIONS: 4Y-01, AM-03, CF-08, CX-02, DE-01, FX-02, FZ-05, GA-03, GF-04, JU-06, KC-11, KE-07, KQ-08, LD-02, LH-01, LJ-01, LX-02, MH-14, OS-01, OU-04, PX-10, SW-02, TN-04, UX-02, VT-01, WB-07, WY-01, X5-02, XK-03, XQ-01.

This instruction applies to Limited Quantities of flammable liquids with no subsidiary hazard in Packing Group III.

The General Packing Requirements of Subsections 2.7.5, 5.0.2 to 5.0.4 (with the exception of 5.0.2.3, 5.0.2.5, 5.0.2.11 and 5.0.2.14.2) must be met except that the packagings do not have to meet the marking and testing requirements of 6.0.4 and Subsection 6.3. Packagings must meet the construction criteria specified in Subsections 6.1 and 6.2 and the test criteria specified in Subsection 6.6.

### Compatibility Requirements

- substances must be compatible with their packagings as required by 5.0.2.6.

### Closure Requirements

- closures must meet the requirements of 5.0.2.7.

### Limited Quantity Requirements

The requirements of Subsection 2.7 must be met including:

- the capability of the package to pass a drop test of 1.2m;
- a 24 hour stacking test;
- inner packagings for liquids must be capable of passing a pressure differential test (5.0.2.9);
- the gross weight of the completed package must not exceed 30 kg.

*Single packagings are not permitted.*

#### COMBINATION PACKAGINGS

Inner Packaging (see 6.1)	Net quantity per inner packaging	Total net quantity per package
Glass	2.5 L	10.0 L
Metal	5.0 L	
Plastic	5.0 L	

#### OUTER PACKAGINGS

Type	Drums						Jerricans			Boxes							
Desc.	Steel	Alu-minium	Ply-wood	Fibre	Plastic	Other metal	Steel	Alu-minium	Plastic	Steel	Alu-minium	Wood	Ply-wood	Recon-stituted Wood	Fibre-board	Plastic	Other metal